



JF Series

What is the prefix for the JF series?

All compatible door and sub master stations must contain the prefix of "JF", ex. JF-DV. What Type of Wire Is Used With the JF Series? The recommended wire for the JF Series is Aiphone's solid, non-shielded two and four-conductor wires, part numbers 871802 and 871804 respectively.

What is a JF ry-1824l?

The JF Series offers a built-in normally open, dry contact (L/L terminals) for door release, with a contact rating of 24v AC/DC, 500mA. For strikes with higher power requirements, or when a normally closed contact is needed for a magnetic lock, the RY-1824L is required.

What type of wire do I need for the JF series?

The recommended wire for the JF Series is Aiphone's solid, non-shielded two and four-conductor wires, part numbers 871802 and 871804 respectively. Click here to view the JF Series installation manual. What Are the Wiring Distances for the JF Series? From the door station to the master station, the maximum wiring distance is 330' (100m).

The JF Series supports 2 video door stations and 3 interior master stations. With built-in picture memory, the system can automatically record visitor calls or can be activated manually. Installation is quick and easy using just 2 wires. Features: ...

The RivetKing JF Series Rubber Nut is used as a removable rivetnut. Installation is performed with the bolt or screw itself. To remove the rivet nut, just remove the bolt or screw. Rubnuts can also be used as vibration isolators to prevent rattle ...

¿El primero en valorar "Jf Turbo Pro-Series Bicicleta Montaña; era MTB 29;" Cancelar la respuesta. Tu dirección de correo electrónico no será publicada. Los campos obligatorios están marcados con *

Contact us for free full report



JF Series

Web: <https://www.raioph.co.za/contact-us/>

Email: energystorage2000@gmail.com

WhatsApp: 8613816583346

